

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F.NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes	
108MP	S5KHMXP03	SF-MM01S-S5KHMV1	MIPI	AF	1/1.33"	TBD	1.6	86	10~∞	TBD	17.8*17.8*8.1	BBR46-01-00 34pin	BBR46-34KBV73		
	S5KHM2SP03-FGX9	SF-KYV6B-V1.0	MIPI	FF	1/1.52"	5.96	1.75	82	10~∞	<1.5%	13.5*13.5*7.82	OK-118RM030/2-35 30pin	OK-118RF030/2-35	CPHY	
64MP	IMX686	SF-YT686A	MIPI	AF	1/1.17"	TBD	1.89	79.8	10~∞	<1.5%	11.8*11.8*6.95	OK-106GM030-035 30pin	OK-106GF030-035		
		SF-FX686AB	MIPI	AF	1/1.73"	TBD	1.89	79.8	10~∞	<2%	13.9*13.25*5.25	OK-118RM030-35 30pin	TBD	CPHY	
		SF-S0686-P60-B V1.0	MIPI	AF	1/1.73"	5.43	1.89	79.8°	10~∞	<1.5%	12*12*6.8	OK-23GM030-04 30pin	OK-23GF030-04		
		SF-OCX686H66	MIPI	AF	1/1.73"	5.56	1.8	D78° H66° V52°	10~∞	<1%	12*12*6.7	AXE834124 34pin	AXE734124		
50MP	IMX766	SF-COQS01 IMX766	MIPI	AF	1/1.52"	TBD	TBD	D80	10~∞	TBD	16.8*17.5*5.55	OK-118RM040-35 40pin	OK-118RP040-35		
		SF-YT766A	MIPI	FF	1/1.52"	5.59	1.88	85.5	10~∞	<1.5%	13.5*13.5*7.82	OK-118RM030/2-35 30pin	TBD		
	S5KJN1SQ03	SF-S05KJN1-H58-V1.0	MIPI	AF	1/2.76"	TBD	1.6	78	10cm~∞	<1%	9.9*9.9*5.57	OK-24M034-04 34pin	TBD		
48MP	IMX586	SF5861-H120	MIPI	FF	1/2"	TBD	2.0	D514;H119;V88	50CM~∞	<-26.5%	13*13*23.5	5055513410 34pin	5055503410		
		SFOX586DY	MIPI	AF	1/2"	4.74	1.79	85	8CM~∞	<1.5%	10.8*10.8*6.5	BM20B(0.8)-30DP-0,4V 30pin	BM20B(0.8)-30DS-0,4V		
		SFOX586Y5B	MIPI	FF	1/2"	TBD	2.0	28.9	TBD	<1.5%	13*13*21.6	5055513410 34pin	505552341		
		SF-OC586-POWER-B V1.1	MIPI	AF	1/2"	TBD	TBD	82	TBD	TBD		10.8*10.8*6	OK-10GM030-04 30pin	OK-10F030-04	
		SF-X586D	MIPI	AF	1/2"	TBD	1.79	D70	15-30mm	<1.5%	10.8*10.8*6	OP27D-P030VA3 30pin	TBD		
		SF-YSJ586A	MIPI	AF	1/2"	TBD	1.79	112	8CM~∞	<-14%	10.8*10.8*6.83	14-5804-030-829+ 30pin	TBD	DPHY	
		SF-C586-A85-B	MIPI	AF	1/2"	4.74	1.79	D79	TBD	<1.5%	10.8*10.8*6	OP27D-P024-VA3(JAE) 24pin	WP27D-P024VA3	xvs=vsync	
	OV48B	SF-WYT48BA-NIR	MIPI	AF	1/2"	TBD	1.79	79	89MM	<1.5%	10.8*10.8*4.27	DF40C-30DP-0.4V 30pin	TBD	No IR filter	
		SF-WYT48BA-IR	MIPI	AF	1/2"	TBD	1.79	79	89MM	<1.5%	10.8*10.8*4.27	DF40C-30DP-0.4V 30pin	TBD	蓝玻璃; D-PHY	
	S5KGM1	SF-S0GM1-CDC320-B	MIPI	AF	1/2.25"	4.74	1.79	79	10CM~∞	<1.5%	10.8*10.8*6.3mm	OK-10GM030-04 30pin	OK-10F030-04		
IMX582	SF-S0582-3A0	MIPI	AF	1/2"	4.8	1.85	78	10CM~∞	<1%	10.8*10.8*6.4mm	OK-10GM030-04 30pin	OK-10F030-04			
24MP	IMX576	SF-T900B V1.2	MIPI	AF	1/2.78"	TBD	1.8	77.8	10CM~∞	<1%	8.8*8.8*6.29	OK-10M030-04 30pin	OK-10F030-04		
		SF-OC576-F29-B	MIPI	AF	1/2.7"	3.81	2.2	78	>10cm	<1%	8.8*8.8*3.85	OK-14M024-04 24pin	OK-14F024-04		
21MP	IMX230	SF-XLW230C-V2	MIPI	AF	1/2.4"	4.71	1.79	79	10CM~∞	<1%	10.8*10.8*3.83	AXT630124 30pin	AXT530124		
		SF-X230D1	MIPI	AF	1/2.4"	TBD	1.79	76	8.5cm~∞	<1.5%	10.8*10.8*3.75	GB042-30P-H10 30pin	TBD		

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F. NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes	
20MP	IMX376	SF-X37621BA	MIPI	AF	1/2. 78"	3. 95	1. 8	80	10CM [∞]	<-1%	8. 8*8. 8*6. 62	AXT630124 30pin	AXT530124		
		SF-IMX376-88-V1	MIPI	FF	1/2. 78"	2. 35	2. 2	122. 6	10CM [∞]	<9. 7%	8. 8*8. 8*6. 96	BBR13-24K6417 24pin	BBR43-24KB533		
		SF-OC376-F29-B V1. 1	MIPI	AF	1/2. 78"	3. 81	2. 2	78	>10cm	<0. 5%	8. 8*8. 8*5. 7	OK-14M024-04 24pin	OK-14F024-04	can replace with IMX476 sensor	
		SF9X376YMY2	MIPI	FF	1/2. 78"	TBD	TBD	TBD	TBD	TBD		8*9*4	WP26-S024VA10-R15000 24pin	WP26-P024VA10-R15000	
		SF-OC376-870-FF	MIPI	FF	1/2. 8"	2. 35	2. 2	117. 3	20CM [∞] 0. 6M	<9. 6%	8. 5*8. 5*7	AXE630124D 30pin	TBD		can replace with IMX476 sensor
		SF-S0376-A11-F V1. 0	MIPI	FF	1/2. 78"	3. 93	2. 2	78	TBD	<1%	7. 6*7. 9*5. 27mm	5055512410 24pin	TBD		
	IMX350	SF-X350A1	MIPI	AF	1/2. 8"	TBD	2. 2	80. 6	10M [∞]	<1%	8. 8*8. 8*5. 3	AXQ2301 30pin	AXQ1302		
IMX476	SF-X476A	MIPI	AF	1/2. 78"	TBD	1. 79	70	10CM [∞]	<1. 5%	10. 8*10. 8*3. 75	GB042-30P-H10 30pin	TBD			
16MP	IMX298	SF-T8298	MIPI	AF	1/3. 06"	TBD	2. 25	D117 / D75	10CM [∞]	TBD	8. 8*8. 8*5. 67	AXQ2301 30pin	AXQ1302		
	IMX298	SF-YT298B-V1	MIPI	AF	1/3. 06"	TBD	2. 2	80. 6	10CM [∞]	<0. 5%	8. 8*8. 8*5. 3	OK-14GM030-04 30pin	OK-14GF030-04		
	IMX298	SF8D298-01	MIPI	AF	1/2. 8"	TBD	2. 2	77. 7	8CM [∞]	<1. 5%	8. 5*8. 5*5. 15	14-5804-030-000-829 30pin	24-5804-030-000-829		
	IMX481	SF-HD481	MIPI	AF	1/3. 1"	TBD	2. 0	77. 6	10CM [∞]	<1. 5%	8. 5*8. 5*5. 2	AXE630124	AXE530124		
	IMX351	SF-S0351-F2-B	MIPI	AF	1/3. 09"	2. 85	2	82	>10cm	<1. 5%	8. 5*8. 5*5. 2mm	OK-14M024-04 24pin	OK-14F024-04		
		SF-OC351-S6680-B	MIPI	AF	1/3. 09"	3. 38	2. 2	82	TBD	<1. 5%	8. 5*8. 5*5. 55	OK-14M030-24 30pin	TBD		
S5K3P3SP	SF-S03P3-A13PRO-F	MIPI	FF	1/3. 1"	3. 56	2. 2	76. 3	40cm	<1%	6. 8*7. 4*4. 68mm	OK-32GM024-04 24pin	TBD			
S5K3P9	SF9R3P9Z9	MIPI	AF	1/3. 1"	3. 5683	2. 0	78	8CM [∞]	<0. 21%	8. 5*8. 5*4. 96	OK-14GM030-04 30pin	OK-14GF030-04			
	SF-YT3P9A	MIPI	AF	1/3"	3. 46	2. 2	80	10CM [∞]	TBD	8. 5*8. 5*6	OK-14GM030-04 30pin	OK-14GF030-04			
	SF-S03L8-G105-B	MIPI	AF	1/3. 06"	3. 46	2. 2	82	10cm [∞] 500cm	<0. 4%	8. 5*8. 5*5. 1mm	OK-10M030-04 30pin	OK-10F030-04			
	SF-R1335BA V1. 0	MIPI	AV	1/3. 2"	3. 57	2. 0	78. 4	10CM [∞]	<-1. 5%	8. 5*8. 5*5. 27	AXT630124 30pin	AXT530124			
	SF-OC13B10-ME40K-B	MIPI	AV	1/3. 06"	3. 34	2. 2	80. 3	5m	<1. 5%	7. 4*4. 8*5. 17	OK-118RM030/2-35 32pin	TBD	LED		
	SF-C13130V-AF-LED	MIPI	AF	1/3. 06"	3. 46	2. 2	79. 8	10CM [∞]	<1. 5%	8. 5*8. 5*5	AXT630124	AXT530124	LED		
	SF-C13130V-ATM01	MIPI	AF	1/3. 06"	3. 79	2. 0	70	10CM [∞]	<1. 0%	8. 5*8. 5*5. 6	0. 5mm golden finger 30pin	FH12-30S-0. 5SH			
SF-C13130V-JC01	MIPI	AF	1/3. 06"	3. 57	2	78	10CM [∞]	<1. 5%	8. 5*8. 5*6. 5	AXK8L24145	AXR7L24127	LED			

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F.NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
13MP	OV13850	SF-C13130V-TS04B	MIPI	AF	1/3.06"	3.46	2.2	80	10CM [~] ∞	<1.5%	8.5*8.5*5.2	AXE634124 34pin	AXE534124	LED
		SF-C13130V-TS04F	MIPI	AF	1/3.06"	3.46	2.2	79.8	10CM [~] ∞	<1.5%	8.5*8.5*5	AXT630124 30pin	AXT530124	
		SF-C13130V-TS05B	MIPI	AF	1/3.06"	3.46	2.2	79.8	10CM [~] ∞	<1.5%	8.5*8.5*5	AXT630124	AXT530124	
		SF-SW3850B	MIPI	AF	1/3.06"	TBD	2.2	79.8	10CM [~] ∞	<1.5%	8.5*8.5*5	AXT630124 30pin	AXT530124	LED
		SF-S7000-OV13850	MIPI	FF	1/3.06"	3.85	2.2	78°	10CM [~] ∞	TBD	8.5*8.5*4.8	AXK8L24124 24pin	TBD	LED
		SF-V3850M7A21 FRONT V1.3	MIPI	FF	1/3.06"	2.33	2.4	125	20CM [~] ∞	<-25%	10*10*6.7	503776-2410 24pin	TBD	
	OV13855	SF-3855C	MIPI	AF	1/3.06"	TBD	2	78.2	10CM [~] ∞	<1.5%	8.5*8.5*5	OK-118RM024-35 24pin	TBD	LED 蓝波IR648
		SF-XR3855A-A0	MIPI	AF	1/3.06"	TBD	2	78.4	8CM [~] ∞	<1.5%	8.5*8.5*4.72	OK-23GM024-04 24pin	TBD	IR FILTER : 使用蓝玻璃
	IMX258	SDA-KK258PA-A0	MIPI	AF	1/3.06"	TBD	2.0	78.4	10CM [~] ∞	<1.5%	8.5*8.5*4.85	IPXE-20641-030E 30pin	IPXE-20642-030E	
		SF9X258R10-C	MIPI	AF	1/3.06"	4.24	2.0	69	10CM [~] ∞	<1%	8.5*8.5*5.6	OK-14GM030-04 30pin	OK-14GF030-04	
		SF-ZX258PA-A0	MIPI	AF	1/3.06"	TBD	2.0	78.4	8CM [~] ∞	<1.5%	8.5*8.5*4.94	OK-14GM030-04 30pin	OK-14GF030-04	
		SF258PC	MIPI	AF	1/3.06"	TBD	2.4	117	10CM [~] ∞	<-7.9%	8.5*8.5*5.77	OK-14GM030-04 30pin	OK-14GF030-04	
	IMX214	SF-IMX214-50-V1	MIPI	AF	1/3.06"	3.35	2.4	137	10CM [~] ∞	<19.35%	8.5*8.5*6.2	AXT630124 30pin	AXT530124	
		SF-SWX214A-A0	MIPI	AF	1/3.06"	TBD	2.4	78.4	10CM [~] ∞	<1.5%	8.5*8.5*4.85	503776-3010 30pin	503772-3010	
		SF8DX214T XLX214A-A0	MIPI	AF	1/3.06"	3.46	2.2	79.8	10CM [~] ∞	<1.5%	8.5*8.5*4.65	14-5804-030-000-829 30pin	24-5804-030-000-829	
		SF-SO214-X10-B	MIPI	AF	1/3.06"	3.85	2.2	83	10CM [~] ∞	<1.5%	8.5*8.5*5.9mm	OK-106M030-35 30pin	TBD	
	IMX135	SF-S0135-S651-B	MIPI	AF	1/3.06"	3.46	2.2	82	10cm [~] 500cm	<0.4%	8.5*8.5*5.4mm	OK-23GM030-04 30pin	OK-23GF030-04	
	IMX328	SF-S0328-A10-B	MIPI	AF	1/3.06"	3.69	2.2	76.7	10CM [~] ∞	<1%	8.5*8.5*5.05mm	504622-2410 24pin	TBD	
	IMX328	SF-S0328-V8-B V1.0	MIPI	AF	1/3.06"	3.46	2.2	82	20CM [~] 0.6M	<1%	8.5*8.5*5.1mm	AXE630124 30pin	AXE530124	
	IMX458	SF-OCIMX458-P2-B	MIPI	FF	TBD	2.35	2.4	117	0.1M [~] ∞	<-15%	16.46*20*8.65	golden finger 25pin	TBD	IR-cat电源线 出货需带 0.8mm端子
S5K3L8	SF-HP3L8PQ-A0	MIPI	AF	1/3.1"	TBD	2	79.9	10CM [~] ∞	<1%	8.5*8.5*4.53	OK-10M030-04 30pin	OK-10F030-04	IR蓝玻璃	
S5K3M5	SF-S5K3M5	MIPI	AF	TBD	TBD	TBD	TBD	TBD	TBD	23.6*11.68*5.77	OK-118RM40-35 40pin	OK-118RF040-35	5倍光学变焦	
S5K3M2XX13	SF-DVS3M2A-A0	MIPI	AF	1/3"	TBD	2.2	79.8	10CM [~] ∞	<1.5%	8.5*8.5*4	WP7-P030VA1-R6000 30pin	TBD		
	SF-ZE3L6A1	MIPI	AF	1/3"	TBD	2	D78.2	10CM [~] ∞	<1%	8.5*8.5*4.6	AXE630124 30pin	AXE530124		

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F.NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
	S5K3L6	SF-SO3L6-WM1101M-F	MIPI	FF	1/3"	3.37	2.2	81.3	40cm	<1%	7.5*7.5*4.6mm	golden finger 25pin	TBD	
		SF-0C3L6	MIPI	AF	1/3"	3.85	2.2	82	10CM~∞	<1.5%	8.55*8.5*4.29	OK-10GM030-04 30pin	OK-10F030-04	
12MP	IMX363	SF363-M14	MIPI	FF	1/2.55"	6.34	5.5	58	TBD	<1.5%	18*18*18.2	BM20B(0.8)-30DP-0, 4V 30pin	BM20B(0.8)-30DS-0, 4V	
	IMX363	SF-X363C	MIPI	AF	1/2.55"	TBD	1.79	68	10CM~∞	<1%	10.8*10.8*6.4	14-5804-030-000-829 30pin	24-5804-030-000-829	
	IMX377	SF-X37721ABA	MIPI	FF	1/2.3"	3.65	3.0	135	10CM~∞	<-30%	18*18*17.15	0.5mm golden finger 30pin	FH12-30S-0.5SH	
	IMX577	SF-X57721BA	MIPI	FF	1/2.3"	3.65	3.0	H105	1M~∞	<-30%	22*14*17.05	0.5mm golden finger 30pin	FH12-30S-0.5SH	
	IMX477	SF-X47721BA V1.0	MIPI	FF	1/2.3"	3.65	3.0	H105	1M~∞	<-30%	22*15*17.05	0.5mm golden finger 30pin	FH12-30S-0.5SH	
	IMX676	SFHX676-1263 V3.1	MIPI	AF	1/1.6"	2.23	2.8	220	30CM~5M	-7.1%	19.65*47.25*31.44	BK13C06-40DP_2-0.35V 46pin	TBD	
	IMX708	SF4V708BA-RP V1.0	MIPI	AF	1/2.43"	2.75	2.2	D120	10CM~∞	<-11.6%	10.8*10.8*7.25	DF37C-30DP-0.4V 30pin	TBD	
	OV12A10	SF2V12A10BA	MIPI	AF	1/2.8"	2.35	2.2	D116	10CM~∞	-7.05%	8.8*8.8*6.8	AXE630124 30pin	AXE530124	
55K4H8	OV08D	SF-SW08DA	MIPI	AF	1/4"	TBD	2	75	10CM~∞	<1%	8.5*8.5*4.55	OK-118RM024-35 24pin	TBD	LED
	HI843	SF8H843A4	MIPI	AF	1/4"	2.92	2.4	75.6	10CM~∞	<-1.5%	8.5*8.5*4.3	55909-0240 25pin	TBD	
	HI846	SF-H846A0	MIPI	AF	1/4"	TBD	2	76.9	10cm~∞	<-1%	8.5*8.5*4.48	YXT-BBIP-30P-02 30pin	TBD	
	S5K4H8	SF-FCS4H8F-A0	MIPI	AF	1/4"	TBD	2.4	120	10CM~∞	<-1.5%	7.5*7.5*5	WP7-P030VA1 30pin	TBD	
		SDA-HPS4H8C-A0	MIPI	AF	1/4"	TBD	2.0	76.9	10CM~∞	<-1.5%	8.5*8.5*4.55	OK-14M024-04 24pin	OK-14F024-04	
		SF-KKS4H8H	MIPI	AF	1/4"	TBD	2.0	74	8CM~∞	<1.5%	8.5*8.5*4.63	OK-23GM030-04 30pin	OK-23GF030-04	
		SF-0C4H8-T6568-F	MIPI	FF	1/4"	2.78	2	77.5	TBD	<1.5%	6.8*6.8*4.8	OK-118RM024 24pin	TBD	
		SF-S04H8-S915-F	MIPI	FF	1/4"	2.67	2.2	80	20CM~0.6M	<1%	6.5*6.5*6.05mm	golden finger 21pin	TBD	
		SF-S04H8-T6525-B	MIPI	AF	1/4"	2.79	2	78	20CM~0.6M	<0.4%	8.5*8.5*4.85mm	OK-10GM030-04 30pin	OK-10F030-04	
		SF-S04H8-A85-B	MIPI	FF	1/4"	1.65	2.2	120	40cm	<10%	8.0*8.0*5.1mm	2074062410 24pin	TBD	
	SF-0C4H8-B	MIPI	FF	1/4"	1.65	2.2	120	20cm~0.6M	<10%	8*8*5.21	505070-2442 26pin	TBD		
	OV8856	SF-HP88562-A0	MIPI	FF	1/4"	TBD	2.0	76.9	35CM~51CM	<1.5%	8.5*8.5*4.05	YXT-BBIP-24P-02 24pin	YXT-BBIP-24S-02	
		SF-WY8856B-A0	MIPI	AF	1/4"	TBD	2.0	76	10CM~∞	<1.5%	8.5*8.5*4.8	BAM04-40083-0500 40pin	BAF04-40083-0500	
SF-0C8856-A10-F PLCC		MIPI	FF	1/4"	2.78	2	77	20cm~0.6M	<1%	6.5*6.5*2.71	OK-14M024-04 24pin	OK-14F024-04	0.21mm蓝玻	

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F.NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
8MP	OV8865	SF-C80130V-TS01F V1.2	MIPI	AF	1/3.2"	3.85	2.2	70	10CM [~] ∞	<1.5%	8.5*8.5*5.6	AXE630124 30pin	AXE530124	
		SF-C80130V-TS01B V1.21	MIPI	AF	1/3.2"	3.46	2.2	80	10CM [~] ∞	<1.5%	8.5*8.5*4.96	AXE634124 34pin	AXE534124	LED
	OV8858	SF-C80140V-TF01 V1.2	MIPI	AF	1/4"	2.94	2.4	75	10CM [~] ∞	<1.5%	8.5*8.5*4.3	0.5mm golden finger 24pin	FH12-24S-0.5SH	
		SF-C80140V-AF-Flash-BTB-L71	MIPI	AF	1/4"	2.56	2.2	85	10CM [~] ∞	<1.5%	8.5*8.5*4.4	AXT630124 30pin	AXT530124	LED
	IMX219	SF-X219J3507BHA	MIPI	AF	1/4"	2.92	2.4	75	10CM [~] ∞	<1%	8.5*8.5*4.3	0.3mm golden finger 25pin	FH26-25S-0.3SHW	
		SF-C8014SY-J3507BH	MIPI	AF	1/4"	2.92	2.4	75	10CM [~] ∞	<1%	8.5*8.5*4.3	0.3mm golden finger 25pin	FH26-25S-0.3SHW	
		SF-X219M821BA	MIPI	FF	1/4"	1.58	2.0	H136	60CM [~] ∞	<-25%	8.5*8.5*4.3	0.5mm golden finger 30pin	FH12-30S-0.5SH	
		SF-X219SN80FY	MIPI	FF	1/4"	2.47	2.0	84	30CM [~] ∞	<1%	6.5*6.5*4.2	0.3mm golden finger 33pin	FH35C-033SHW-0.5SH	
		SF-X219650Y	MIPI	FF	1/4"	TBD	2.2	120	20CM [~] ∞	<15%	8*8*5.3	AXT630124 30pin	AXT530124	
		SF-S0219-F2 PUIS-F	MIPI	FF	1/4"	2.85	2	78	20CM [~] 0.6M	<1.5%	6.5*6.5*6.2mm	golden finger 21pin	TBD	
		SF-S0219-S5590-B	MIPI	AF	1/4"	2.85	2	76.9	>10cm	<1.5%	8.5*8.5*5.15mm	OK-10GM030-04 30pin	OK-10F030-04	
		SF3X219BA-RP	MIPI	AF	1/4"	2.92	2.4	75.6	10cm [~] ∞	<-1%	8.5*8.5*4	golden finger 15pin	TBD	
	IMX219+BF20A1	SF-S0219-S6268-B V2.0	MIPI	AF	1/4"	2.94	2	75.6	TBD	<1.5%	8.5*8.5*5.35mm	OK-22M030-04 30pin	TBD	LED
	IMX415	SF-X41521BA V1.0	MIPI	FF	1/2.8"	2.8	2.0	H129	1M [~] ∞	<-40%	22*15*18.45	0.5mm golden finger 30pin	FH12-30S-0.5SH	
		SF-ZN4151	MIPI	AF	1/2.8"	3.1	2.4	D93	TBD	<0.7%	20*24*9.2	golden finger 30pin	TBD	
	IMX317	SF-X31721BA	MIPI	FF	1/2.5"	3.2	1.8	H116	1M [~] ∞	<-40%	24*16*24.04	0.5mm golden finger 30pin	FH12-30S-0.5SH	
	IMX334	SFOX334T1	MIPI	FF	1/1.8"	TBD	TBD	TBD	TBD	TBD	38*38*32	golden finger 30pin	TBD	
	IMX274	SF-TE8025	MIPI	FF	1/2.5"	2.5	2.4	D16/H14/V8.2	0.5M [~] ∞	<-40%	24*16*24.04	golden finger 30pin	FH12-30S-0.5SH	
	IMX678	SF3X678BA	MIPI	FF	1/1.8"	4	2	D133	1M [~] ∞	<-35%	26*20*24.34	golden finger 30pin	TBD	
	HI-843	SF3HI843BY	MIPI	FF	1/4"	TBD	2.4	D87.9	40cm [~] ∞	<1.5%	8.5*8.5*3.95	golden finger 24pin	TBD	
	OV5675	SF-HP5675A	MIPI	FF	1/4"	TBD	2.4	74.5	10CM [~] ∞	<1.5%	8.5*8.5*3.85	OK-22M024-04 24pin	TBD	
	OV5695	SF-SR5695A-A0	MIPI	AF	1/4"	TBD	2.0	74.06	10CM [~] ∞	<1.5%	8.5*8.5*4.89	OK-14GM030-04 24pin	OK-14GF030-04	
	OV5695	SF56953-A0	MIPI	FF	1/4"	TBD	2.2	87	27CM [~] 74CM	<1.5%	6.5*6.5*4.2	OK-14GM030-04 25pin	OK-14GF030-04	
	OV5695	SF-WY5695A-A0	MIPI	AF	1/4"	TBD	2.0	76.5	10CM [~] ∞	<1.5%	8.5*8.5*4.75	BAM04-24083-0502	BAF04-24083-0502	

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F. NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
	OV5695	SF-ZE56951F	MIPI	FF	1/4"	TBD	2.2	84	28CM~65CM	<1.5%	8.5*8.5*4.75	QG1324421Y-M08-7H 24pin	QG2324421Y-M08-7H	
	OV5695	SF-RSD56951	MIPI	FF	1/4"	1.925	2.2	D120	20CM~∞	TBD	6.5*6.5*5.2	OK-14M024-04 24pin	OK-14F024-04	
	OV5648	SF-C50140V-FF-MIPI-D100-L43	MIPI	FF	1/4"	2.3	2.2	100	15CM~30CM	<-10%	9*9*5.5	AXT624124 24pin	AXT524124	
	OV5648	SF-C50140V-MIPI-BTB-L30 V1.0	MIPI	FF	1/4"	1.8	2	H125	9cm	<-25%	9*9*14.7	AXT624124 24pin	AXT524124	
	OV5648	SF-U502P-5648BJ	MIPI	FF	1/4"	TBD	TBD	72	60cm	TBD	13.55*13.55*7.97	golden finger 25pin	TBD	
	OV5647	SF-C50140V-V8B	MIPI	AF	1/4"	3.75	2.8	60	10M~∞	<1%	8.5*8.5*5.1	OK-14M024-04 24pin	OK-14F024-04	
	OV5647	SF-C50140V-DX7707B	MIPI	AF	1/4"	3.75	2.8	60	10M~∞	<1%	8.5*8.5*5.1	OK-14M024-04 24pin	OK-14F024-04	
	OV5647	SF-C50140V-827B	MIPI	AF	1/4"	3.75	2.8	60	10M~∞	<1%	8.5*8.5*5.1	OK-06M030-04 30pin	OK-06F030-04	
	OV5647	SF-WK5647A	MIPI	AF	1/4"	TBD	2.8	H67.4	10M~∞	<1%	8.5*8.5*4.92	AXT630124 30pin	AXT530124	
	OV5647	SF-CR5647AY	MIPI	AF	1/4"	TBD	2.8	70	10M~∞	<1%	8.5*8.5*5.2	BBR13-30K6417 30pin	TBD	
	OV5640	SF3V5640BA-RP V1.0	MIPI	AF	1/4"	3.4	2.8	65.5	10CM~∞	<-1%	8.5*8.5*4.6	golden finger 15pin	TBD	
	OV5640	SF-C50140V-MIPI-FF-D105 V1.2	MIPI	FF	1/4"	2.3	2.2	D105	60M~∞	<-10%	9*9*5.5	AXK824145 24pin	AXK724127	
	OV5640	SF3V5640BY-ESP / SF56403	DVP	FF	1/4"	2.6	2.4	D80	TBD	<-1.2%	10*10*10.7	golden finger 24pin	TBD	ESP32
	OV5645	SF-C50140V-MIPI-FF-72L	MIPI	FF	1/4"	3.0	2.2	H62	60M~∞	<-1.5%	8.5*8.5*4.5	AXE630124 30pin	AXE530124	
	OV5645	SF-C50140V-MIPI-FF-24L	MIPI	FF	1/4"	3.0	2.2	H62	60M~∞	<-1.5%	8.5*8.5*5.0	AXE630124 30pin	AXE530124	
	OV5645	SF-C50140V-M7B	MIPI	AF	1/4"	3.75	2.8	60	10M~∞	<1%	8.5*8.5*5.3	0.3mm golden finger 25pin	FH26-25S-0.3SHW	
	OV5645	SF-C50140V-J7208B	MIPI	AF	1/4"	3.75	2.8	60	10M~∞	<1%	8.5*8.5*5.1	OK-10M024-04 24pin	OK-10F024-04	
	OV5645	SF-C50140V-ATV01	MIPI	AF	1/4"	3.37	2.8	65	10M~∞	<1%	8.5*8.5*5	AXK824145 24pin	AXK724127	
	OV5645	SF-AOV5645-MIPI-FF-D75	MIPI	AF	1/4"	3	2.4	75	60CM~∞	<1.5%	8.5*8.5*4.6	OK-14GM024-04 24pin	OK-14GF024-04	
	OV5640	SF-C50140V-TCL01	MIPI/DVP	AF	1/4"	3.37	2.8	70	10CM~∞	<1%	8.5*8.5*5.1	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV5640	SF-C50140V-JH05	DVP	FF	1/4"	2.8	2.4	H85	40CM~200CM	<13%	38*38*22.6	FH12-20S-0.5SH 20pin	0.5mm Flat FPC 20pin	IR CUT Switch
	OV5640	SF-C50140V-GD02-H25	MIPI	FF	1/4"	8.0	2.0	H25	5M	<1%	13.5*13.5*24.8	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV5640	SF-C50140V-GD01-H34	MIPI	FF	1/4"	6.0	2.0	H36	5M	<-2%	13.5*13.5*24.7	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV5640	SF-C50140V-FF-D100-L43	MIPI	FF	1/4"	2.3	2.2	100	15CM~30CM	<-10%	9*9*5.5	AXT624124 24pin	AXT524124	

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F. NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
5MP	OV5640	SF-C50140V-FF-D100-25L	DVP	FF	1/4"	2.3	2.2	100	60CM~80CM	<-10%	9*9*5.5	0.5mm golden finger 24pin	XF3M-2415-1B	
	OV5640	SF-C50140V-WZ02	DVP	FF	1/4"	2.79	2.4	H76	30CM~250CM	<-25%	22*14*18.6	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV5640	SF-C50140V-WZ01	DVP	FF	1/4"	2.79	2.4	H76	30CM~250CM	<-25%	22*14*18.6	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV5640	SF-C50140V-PS01	DVP	FF	1/4"	2.0	2.5	H110	60CM~∞	<-88%	9*9*12.5	0.3mm golden finger 23pin	FH26-23S-0.3SHW	
	OV5640	SF-C50140V-PAR-FF-D67-100L	DVP	FF	1/4"	3.37	2.8	65	40CM~150CM	<1%	8.5*8.5*4.9	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV5640	SF-C50140V-AD01	DVP	AF	1/4"	3.75	2.8	60	10CM~∞	<1%	8.5*8.5*5	AXK824145 24pin	AXK724127	
	OV5640	SF-C5014USB-3518-ICFPC	DVP	AF	1/4"	3.37	2.8	67	10CM~∞	<-1%	8.5*8.5*5	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV5640	SF-AOV5640-TS02 V1.2	MIPI/DVP	AF	1/4"	3.37	2.8	65	10CM~∞	<1%	8.5*8.5*5.5	AXK824145 24pin	AXK724127	LED
	OV5640	SF-C50140V-SR01	DVP	AF	1/4"	3.37	2.8	65	10CM~∞	<1%	8.5*8.5*5	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV5640	SF-C50140V-GRS01	DVP	AF	1/4"	3.37	2.8	60	10CM~∞	<1%	8.5*8.5*5	BAM04-24153-0502	BAF04-24153-0502	
	OV5640	SF-C50140V-DVP-AF-L164	DVP	AF	1/4"	3.37	2.8	67	10CM~∞	<-1%	8.5*8.5*5	AXK824145	AXK724127	
	OV5640	SF-C50140V-AF-PAR-80L-ZIF	DVP	AF	1/4"	3.37	2.8	67	10CM~∞	<1%	8.5*8.5*5	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV5640	SF-C50140V-AF-PAR-60L-ZIF	DVP	AF	1/4"	3.37	2.8	67	10CM~∞	<1%	8.5*8.5*5	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV5640	SF-C50140V-AD06	DVP	AF	1/4"	3.3	2.8	67	10CM~∞	<1%	8.5*8.5*5	AXK824145 24pin	AXK724127	
	OV5640	SF-C50140V-PS01	DVP	FF	1/4"	2	2.5	110	60CM~∞	<-88%	9*9*3.6	0.3mm golden finger 23pin	FH26-23S-0.3SHW	
	OV5640	SF-AOV5640-ATV00	MIPI	AF	1/4"	3.37	2.8	65	10CM~∞	<1%	8.5*8.5*5	AXK824145	AXK724127	
	OV5640	SF-AOV5640-MIPI-AF-70L V1.1	MIPI	AF	1/4"	3.37	2.8	67	10CM~∞	<1%	8.5*8.5*5	AXK824145 24pin	AXK724127	
	OV5640	SF-C50140V-MIPI-FF-H125	MIPI	FF	1/4"	1.8	2	125	60CM~∞	<-25%	9*9*14.7	AXK824145 24pin	AXK724127	
	OV5640	SF-AOV5640-MIPI-FF-M12	MIPI	FF	1/4"	2.15	2.4	H105	50CM~∞	<-20%	33*28*14.7	AXK824145 24pin	AXK724127	
	OV5640	SF-SQ5V02A	DVP	AF	1/4"	3.35	2.8	68.2	10CM~∞	<1%	8.5*8.5*4.8	FX12B-40P-0.4SV 40pin	TBD	
	OV5640	SF-AOV5640-TS03	MIPI	AF	1/4"	3.37	2.8	65	10CM~∞	<1%	8.5*8.5*5.5	AXK8L24145 24pin	AXK7L24127	
	OV5640	SF-QSJ56401	MIPI	FF	1/4"	3.29	2.8	68.7	30CM~∞	<1%	8.5*8.5*4.8	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV5640	SF-V5640PA60LA V1.0	DVP	AF	1/4"	3.37	2.8	67	10CM~∞	<-1%	8.5*8.5*5	golden finger 24pin	TBD	
OV5640	SF-V56401Y	MIPI	AF	1/4"	TBD	2.8	68.7	200CM	<1%	8.5*8.5*3.97	golden finger 24pin	TBD		

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F.NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
	GC5025	SF-C5025GC-U680BH V1.1	MIPI	FF	1/4"	2.63	2.2	60	45CM [∞]	<1%	8.5*8.5*4.25	OK-23GM030-04	OK-23GF030-04	
		SF-C5025GC-U680BAF V1.2	MIPI	AF WV511	1/4"	2.63	2.2	60	10CM [∞]	<1%	8.5*8.5*4.2	OK-23GM030-04	OK-23GF030-04	
		SF-C5025GC-1711BH V1.1	MIPI	FF	1/4"	2.63	2.2	60	45CM [∞]	<1%	8.5*8.5*4.1	OK-23GM030-04	OK-23GF030-04	
	GC5024	SF-C5024GC-MIPI-AF V1.1	MIPI	AF WV511	1/4"	3.37	2.8	67	10CM [∞]	<1%	8.5*8.5*5	AXT630124	AXT530124	
	GC5035	SF-SW503510	MIPI	FF	1/5"	TBD	2.4	84°	40cm	<1.5%	5.5*5.5*3.77	OK-118RM024-35 24pin	TBD	
		SF-G5035S60AY	MIPI	AF	1/5"	2.27	2.2	76	10CM [∞]	<1.5%	8.5*8.5*4.6	OK-06M030-04 30pin	OK-06F030-04	
		SF-G5035S60FY	MIPI	FF	1/5"	2.01	2.4	84.1	TBD	<1.5%	5.5*5.5*3.7	OK-06M030-04 30pin	OK-06F030-04	
		SF-ZC-K9-5MAF	MIPI	AF	1/5"	3.128	2.8	60.2	10CM [∞]	<1.6%	27.5*11*5	0.5mm golden finger 24pin	FH12-24S-0.5SH	LED
	S5K5E2	SF-S05E2-S920-B	MIPI	AF	1/5"	2.26	2	76	>10cm	<1.5%	8.5*8.5*4.80mm	OK-10M030-04 30pin	OK-10F030-04	
		SF-S05E2-S5790-F	MIPI	FF	1/5"	2.26	2.2	76	40cm	<1.5%	6.5*6.5*4.60mm	OK-10GM024-04 24pin	TBD	
		SF-S05E2-TY005-F	MIPI	FF	1/5"	2.26	2.2	76	40cm	<1.5%	6.5*6.5*5.80mm	golden finger 21pin	TBD	
	S5K5E8	SF-YKS5E81	MIPI	FF	1/5"	TBD	2.4	70.8	29cm~64cm	<1%	6.5*6.5*3.9	14-5861-024-024-829 24pin	TBD	
		SF-S05E8-B860-F	MIPI	FF	1/5"	2.34	2.4	76	20CM~0.6M	<1.5%	6.5*6.5*4.70mm	CFPC0310-25RL-TAG 25pin	TBD	
		SF-S05E8-L6003-B	MIPI	AF	1/5"	2.54	2.4	76	20CM~0.6M	<1%	8.0*8.0*5.0mm	golden finger 31pin	TBD	LED
		SF-SWS5E82-A0	MIPI	FF	1/5"	TBD	2.2	73.6	29cm~61cm	<1.5%	6.5*6.5*3.9	503776-2410 24pin	TBD	IR蓝玻璃
	OV5693	SF-AOV5693-S8009B-Z	MIPI	FF	1/4"	3.85	2.2	78	TBD	<1.5%	8.5*8.5*5.2	OK-23GM024 24pin	TBD	
	BF2553	SF-A13-TABMAX	MIPI	FF	1/5"	2.35	2.2	73.5	20cm~60cm	<1%	5*5*4	golden finger 31pin	TBD	LED
	OS05A20	SF20S5A20BA	MIPI	FF	1/2.7"	1.96	1.8	D175	30CM [∞]	<-30%	13*13*8	FH12-30S-0.5SV 30pin	TBD	
	GC05A2	SF-SW05A23	MIPI	FF	1/5"	TBD	2.2	D75	30CM [∞]	<1.5%	5*5*4.1	OK-118RM030/2-35 30pin	TBD	
4MP	OV4689	SF-AOV4689SY-02	MIPI	FF	1/3"	1.08	2.2	H208	20CM [∞]	<-70%	16*16*12.7	0.5mm golden finger 24pin	FH12-24S-0.5SH	
		SF-KK46892-A0	MIPI	FF	1/3"	3.0	2.0	140/110/56	2.25M~4.55M	TBD	26*20.2*17.85	GB042-24P-H10 24pin	GB042-24S-H10	IR CUT Switch
		SF-S0A4689009-M2 V1.1	MIPI	FF	1/3"	2.52	2.4	120	0.1M [∞]	<16%	20*16.7*16.1mm	OK-14M030-04 30pin	OK-14F030-04	IR-CUT
		SF-0C4689-IRCUT	MIPI	FF	1/3"	2.35	2.4	117	0.1M [∞]	<-15%	16.46*20*8.65	golden finger 25pin	FH26-S-0.3SHW	IRCUT
	GC4663	SF-RCWT9B-F0	MIPI	FF	1/3"	1.74	2.4	129.5	0.1M [∞]	<9.8%	16.46*20*8.65	golden finger 25pin	TBD	IR CUT Switch

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F.NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
	AR0500	SF-FYC500A	MIPI	FF	1/2.7"	TBD	1.8	D125	TBD	<-60%	15.3*15.3*22.7	golden finger 24pin	TBD	
3MP	OV3660	SF-300-RSM	DVP	FF	1/5"	TBD	2.8	D130, H100	40CM~∞	<-5%	8*8*11	golden finger 24pin	TBD	
	OV3660	SF2V3660BY	DVP	FF	1/5"	2.86	2.8	68.6	TBD	TBD	8*8*4.4	golden finger 24pin	TBD	
	OV3660	SF3V3660BY-ESP	DVP	FF	1/5"	2.38	2.4	70.8	TBD	TBD	8*8*4	golden finger 24pin	TBD	
	OV3640	SF-C30140V-FX02	DVP	AF	1/4"	3.37	2.8	65	10CM~∞	<1%	8.5*8.5*5	golden finger 24pin	FH12-24S-0.5SV(55)	
	OV3640	SF-DL300	DVP	FF	1/4"	3.81	2.8	65.1	TBD	<1%	8*8*4.5	golden finger 24pin	TBD	
	AR0330	SF-AR0330MI-WR01	MIPI	FF	1/3"	3.6	2	72	1M~∞	<15%	12.9*12.9*22.7	0.5mm golden finger 24pin	FH12-24S-0.5SH	
		SF-AR0330-LZY03	DVP	FF	1/3"	2.4	2.35	H110	40CM~300CM	<-14%	9*9*17	0.5mm golden finger 24pin	FH12-24S-0.5SH	
OG02B1B	SF-C20130V-GB&M-D&M-FPC	MIPI/DVP	FF	1/2.9"	1.96	1.8	D166	45CM~∞	<-30%	13.9*22*14.3	5.0mm golden finger 30pin	FH12-30S-0.5SH(55)		
OG02B10	SF-C20130V-GB&C-D&M-FPC	MIPI/DVP	FF	1/2.9"	1.96	1.8	D166	45CM~∞	<-30%	13.1*22*14.3	5.0mm golden finger 30pin	FH12-30S-0.5SH(55)		
GC2093	SF-G53MPI-FHD-MN01	MIPI	FF	1/2.9"	2.4	2.2	D166	10cm~∞	<24%	27*18*17.8	FH26-25S-0.3SHW 25pin	FH35C-25S-0.3SHW		
OV2680	SF-YK26801-SID	MIPI	FF	1/5"	TBD	2.4	83	24CM~∞	<-1%	6.5*6.5*3.6	BM040-I24B-C08-A 24pin	BF040-I24B-C08-A		
IMX290	SF-YFX2901-A0	MIPI	FF	1/2.8"	TBD	1.8	140	TBD	<-51%	13.2*13.2*23.3	golden finger 24pin	TBD		
OV2740	SF-V274021BA	MIPI	FF	1/6"	1.753	2.4	82	40CM~∞	<-1%	5*5*3.35	0.5mm golden finger 24pin	FH12-24S-0.5SH		
OS02G10	SF-OT1892-FV1	MIPI	FF	1/2.9"	3.0	2.2	141	TBD	<20%	10*10*14.97	14-5804-024-000-829 24pin	24-5804-024-000-829		
OV2735	SF-OV2735A49	MIPI	FF	1/2.7"	3.3	2.75	H109	60M~∞	<11%	9*9*16	AXT624124 24pin	AXT524124		
	SF-C2013USB-3023-PCB	DVP	FF	1/2.7"	3.6	2.0	105	1M~∞	<-15%	30*23*24	2-1734742-0 20pin	0.5mm Flat FPC		
OV2718	SF-C20130V-MIPI-FPC	MIPI	FF	1/2.9"	3.14	2.2	90	1M~∞	<-5%	10.5*10.5*10.3	0.5mm golden finger 24pin	FH12-24S-0.5SH		
	SFLOV20-DT639-F1	MIPI	FF	1/2.9"	3.0	2.2	139	1M~∞	<16%	20*20*15.5	OK-10M030-04 30pin	OK-10F030-04	IR CUT Switch	
OV2710	SF-C20130V-HQ03	DVP	FF	1/2.7"	3.3	2.75	130	1M~∞	<11%	16.5*10.5*16.4	14-5804-020-000-829	24-5804-020-000-829		
	SF-C20130V-FPC-H230	DVP	FF	1/2.7"	1.44	1.8	H230	30CM~∞	<19.2%	14*14*13.8	OK-23GM024-04 24pin	OK-23GF024-04		
	SF-C20130V-CY785	DVP	FF	1/2.7"	3.37	2.2	H112	1M~∞	<20%	Ø24*22.8	0.5-CX-28PWB	0.5mm Flat FPC 28pin		
	SF-C20130V-CY01	DVP	FF	1/2.7"	3.24	2.5	H115	60CM~∞	<-10.5%	Ø24*23.3	0.5mm golden finger 28pin	0.5mm Flat FPC 28pin		
	SF-V27102	DVP	FF	1/2.7"	TBD	2.6	D73° / H62° / V39°	200CM	H:-1.5%; V:-0.8%		10*10*8.55	TBD	TBD	

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F. NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
2MP	OV2643	SF-C20140V-JH02	DVP	FF	1/4"	3.6	2.0	65	60CM~∞	<-25%	38*38*24	0.5mm Flat FPC 20pin	FH12-240-0.5SH	带IR CUT Switch
		SF-C20140V-JH01	DVP	FF	1/4"	3.75	2.6	60	60CM~∞	<1%	8*8*6	0.5mm golden finger	FH12-24S-0.5SH	
		SF-C20140V-AD07	DVP	FF	1/4"	3.37	2.8	65	20CM~40CM	<1%	8*8*5	GB040-24P-H15	GB040-24S-H15	
	OV2640	SF-C20140V-SY02-D15	DVP	FF	1/4"	1.6	2.3	15	TBD	<-1%	22*15*23.6	0.5mm golden finger 24pin	FH12-24S-0.5SH	
		SF-C20140V-CHSB02	DVP	FF	1/4"	3.37	2.8	65	27CM~35CM	<1%	8.5*8.5*5.3	0.5mm golden finger 24pin	FH12-24S-0.5SH	
		SF-C20140V-JE01	DVP	FF	1/4"	2.15	2.4	H115	60CM~∞	<-12%	14*14*14.7	0.5mm golden finger 24pin	FH12-24S-0.5SH	
		SF-V26402	DVP	FF	1/4"	TBD	2.8	160	200CM	<-5%	13.4*13.4*8.6	golden finger 24pin	TBD	
		SF-FV26409	DVP	FF	1/4"	TBD	2.8	68	80CM	<1%	9*9*4.35	golden finger 24pin	TBD	
		SF-FV26404	DVP	FF	1/4"	TBD	2.8	65	80CM	<1%	8*8*3.86	golden finger 24pin	TBD	
		SF4V2640BA-ESP-M12	DVP	FF	1/4"	1.2	2.25	D130	20CM~∞	<-12%	13.9*13.9*14.42	golden finger 24pin	TBD	
		SF4V2640BA-ESP-S	DVP	FF	1/4"	1.4	2.2	D135	10CM~∞	<-10%	8.5*8.5*5.25	golden finger 24pin	TBD	
	GC2235	SF-C2235GC-L100-F19-B V1.0	MIPI	FF	1/5"	2.65	2.2	67	30CM~200CM	<1%	8.5*8.5*4.3	0.3mm golden finger	FH26-39S-0.3SHW	
		SF-C2235GC-L100-F11B V1.0	MIPI	FF	1/5"	2.65	2.2	67	30CM~200CM	<1%	8.5*8.5*4.3	0.3mm golden finger	FH26-39S-0.3SHW	
		SF-C2235GC-J3507F V1.0	MIPI	FF	1/5"	2.66	2.8	60	60CM~∞	<1%	6.5*6.5*4.5	0.3mm golden finger	FH26-21S-0.3SHW	
	GC2145D	SF-C2145GC-RH01 V1.0	DVP	FF	1/5"	2.75	2.8	60	60CM~∞	<1%	6.5*6.5*4.2	AXK824145 24pin	AXK724127	
	GC2145D	SF-C2145GC-J7F V1.0	DVP	FF	1/5"	2.75	2.8	60	30CM~∞	<1%	6.5*6.5*4.3	0.3mm golden finger 21pin	FH26-21S-0.3SHW	
	GC2145D	SF-C2015GC-HBD01 V1.0	DVP	FF	1/5"	2.75	2.8	60	60CM~∞	<1%	6.5*6.5*4.2	AXK824145 24pin	AXK724127	
	GC2145M	SF-GC2145AD322	MIPI	FF	1/5"	2.59	2.8	64	30CM~∞	<1%	6.5*6.5*4.5	OK-14M030-04 30pin	OK-14F030-04	
	GC2145	SF-SW21452	MIPI	FF	1/5"	2.7	2.8	66	TBD	<1.5%	6.5*6.5*4.2	golden finger 25pin	TBD	
	GC2145	SF-C2145GC-MIPI-FF-BTB	MIPI	FF	1/5"	2.66	2.8	71	45CM	<-1%	8.5*8.5*4.02	AXE630124 30pin	AXE530124	
GC2145	SF-XL21451-A0	DVP	FF	1/5"	TBD	2.4	D70.8	33CM~∞	<2%	6.5*6.5*3.3	golden finger 21pin	BL125-21RL-TA3G		
GC2145	SF3G2145BC-ESP	DVP	FF	1/5"	2.27	2.2	73	40cm	<1.5%	6*6*4	golden finger 24pin	TBD		
GC2053	SF-C2013GC-MIPI-D130	MIPI	FF	1/5"	2.9	2.4	130	50CM~∞	<-20%	9*9*6.32	0.5mm golden finger 24pin	FH12-24S-0.5SH		
IMX307	SF-YFX3071-A0 PD	MIPI	FF	1/2.8"	2.9	2.0	140/110/56	68.2CM~∞	<-50%	22*16.2*23.7	0.5mm Flat FPC 24pin	0.5-2X-24PWB		

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F. NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
	IMX290	SF-X29021BA V1.0	MIPI	FF	1/2.8"	2.95	2.5	H80	50CM \sim ∞	<-1%	22*15*16.03	0.5mm golden finger 30pin	FH12-30S-0.5SH	
	IMX132	SF-SMX1321-A0	MIPI	FF	1/6.95"	TBD	2.2	34.63	20CM \sim 23CM	<1.5%	5.5*5.5*4.55	0.3mm golden finger 25pin	FH26-25S-0.3SHW	
	IMX462	SF2X462BA V1.0	MIPI	FF	1/2.8"	4	2.1	D100	70cm \sim ∞	<-8.3%	15*15*9.43	golden finger 30pin	FH12-30S-0.5SH	
	IMX462	SF2X462A51	MIPI	FF	1/2.8"	3.9	2.8	H70/H38/H59	235CM	<-0.12%	15*15*23	golden finger 22pin	TBD	
	SC201CS	SF-OCSC201-A13-POWER SUB	MIPI	FF	1/5"	2.85	2.4	75	TBD	<1.5%	6.5*6.5*4.1	OK-128GM024/2-35 24pin	TBD	
	OV2312	SF3V2312BA V1.0	MIPI/DVP	FF	1/2.9"	1.96	1.8	166	45CM \sim ∞	<-30%	13.1*13.1*7.9	golden finger 30pin	TBD	
	GC02M1	SF-SW02M22	MIPI	FF	1/5"	TBD	2.4	84.1	40cm	<1.5%	8.5*8.5*5.1	AXE630124 30pin	AXE530124	
		SF-GC20-00K9-F3	MIPI	FF	1/5"	2.52	2.8	70	10cm \sim 30cm	<1%	6.5*6.5*2.6	AXT624124 24pin	AXT524124	
	OV02B10	SF-V02B101	MIPI	FF	1/5"	TBD	2.8	66°	40cm \sim ∞	<1.5%	6.5*6.5*4.25	golden finger 24pin	0.5S-2X-24PWB (CCDX)	
		SF-V02B102	MIPI	FF	1/5"	TBD	2.8	83°	40cm \sim ∞	<1.5%	6.5*6.5*3.65	golden finger 24pin	0.5S-2X-24PWB (CCDX)	
		SF-PC0SW0002A	MIPI	AF	1/5"	1.96	2.4	D83.2	37 \sim 43mm	<1%	6.5*6.5*3.7	YXT-BB10-24P-02 24pin	TBD	
	BF2253L	SF-S02253L-S50712B-F	MIPI	FF	1/5"	2.9	2.8	61.5	20CM \sim 0.6M	<1.5%	6.5*6.5*5.0mm	golden finger 25pin	TBD	
		SF-S02253CS-A10	MIPI	FF	1/5"	2	2.4	84	2cm	<1.5%	6.5*6.5*4.34mm	OK-23GM024-04 24pin	OK-23GF024-04	
		SF-S01002S-V1.1	MIPI	FF	1/5"	2	2.4	72	60cm	<1.5%	40*10.8*5.08mm	KH-FG0.5-H2.0-40PIN	TBD	LED
	BF2257	SF-S02257CS-A10	MIPI	FF	1/5"	2	2.4	86	20CM \sim 0.6M	<1.5%	6.5*6.5*4.34mm	OK-23GM024-04 24pin	OK-23GF024-04	
		SF-S02257CS-H6-F	MIPI	FF	1/5"	2.85	2.8	61.5	20CM \sim 0.6M	<0.4%	6.5*6.5*4.45mm	CFPC0310-25RL-TAG 25pin	TBD	
1.3MP	SC132GS	SF-S0132SAOMA V1.0	MIPI	FF	1/4"	4.24	6	D50	120mm \sim 250mm	<2%	6.5*6.5*6.67	14-5861-016-024-829+ 16pin	TBD	
	OV9782	SF-V978221BA	MIPI/DVP	FF	1/4"	1.66	2.2	120	30CM \sim ∞	<-10%	7*87*5.12	AXE624124 30pin	AXE524124	
	OV9782	SF-OC9782D	MIPI	FF	1/4"	1.22	2	140	70cm \sim 350cm	<-33.7%	13.43*13.43*2.7	golden finger 24pin	TBD	
	OV9732	SF-C1014USB-D65-FPC38L	MIPI	FF	1/4"	3.37	2.8	67	15CM \sim 40CM	<1%	8*8*4.85	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV9732	SF-C10140V-YXD01	MIPI	FF	1/4"	0.95	2.0	150	50CM \sim ∞	<1%	8*8*3.6	0.3mm golden finger 23pin	FH26-23S-0.3SHW	
	OV9732	SF-C10140V-JA01-D55	MIPI	FF	1/4"	4.39	2.4	55	60CM \sim ∞	<1%	8*8*5.65	0.3mm golden finger 23pin	FH26-23S-0.3SHW	
	OV9732	SF-C10140V-DVP-8585-D80	DVP	FF	1/4"	3.25	2.8	80	15CM \sim 40CM	<1%	8*8*4.5	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV9712	SF-C10140V-TBD01	DVP	FF	1/4"	3.37	2.8	65	60CM \sim ∞	<1%	8*8*4.9	0.3mm golden finger	FH26-25S-0.3SHW	

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F. NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
1MP	OV9712	SF-C10140V-SY01-D15	DVP	FF	1/4"	1.6	2.3	15	16.3CM	<-1%	22.2*15*23.6	0.5mm golden finger	FH12-24S-0.5SH	
	OV9712	SF-C10140V-PAR-D65	DVP	FF	1/4"	3.37	2.8	65	60CM~∞	<1%	8*8*4.9	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV9712	SF-C10140V-LA01	DVP	FF	1/4"	1.0	2.8	H140	100CM~∞	<-45%	13*13*12.8	0.5mm golden finger	FH12-24S-0.5SH	
	OV9712	SF-C10140V-JA02	DVP	FF	1/4"	3.6	2.8	90	80CM~∞	<10%	25*14*16.7	CFPC0510-24RL-MGA	0.5mm Flat FPC 24pin	
	OV9712	SF-C10140V-H180	DVP	FF	1/4"	1.2	1.8	H180	60CM~∞	<-115%	13.2*13.2*17.9	0.5mm golden finger	FH12-24S-0.5SH	
	OV9712	SF-C10140V-FF-Z1F-H150	DVP	FF	1/4"	1.58	2.5	H150	60CM~∞	<-20%	11.4*11.4*15.3	0.5mm golden finger	FH12-24S-0.5SH	
	OV9712	SF-C10140V-BZ01	DVP	FF	1/4"	2.3	2.25	120	60CM~∞	<5.6%	13.2*13.2*18.8	0.5mm golden finger 24pin	FH12-24S-0.5SH	
	OV9281	SF-C10140V-B&W-H80	MIPI	FF	1/4"	2.2	2.0	H80	60CM~∞	<-1%	8*8*10.9	AXT624124	AXT524124	B&W
	OV9281	SF-AOV9281	MIPI	FF	1/7.5"	2.3	2.2	H85	50CM~∞	<-10%	8*8*5.61	AXT624124 24pin	AXT524124	NO Filter
	HM1375	SF-C1014HM-PAR-8.5X8.5-45L	DVP	FF	1/4"	3	2.2	76	50CM~200CM	<-1%	8.5*8.5*4.3	0.5mm golden finger 20pin	FH12-20S-0.5	
	OV9282	SF-XNXS9282V10V IR650nm	MIPI	FF	1/4"	TBD	2.0	150	10CM~∞	<27%	9*9*7	503776-2420 24pin	503772-2420	IR 650
		SF-XNXS9282IR850	MIPI	FF	1/4"	TBD	2.0	150	10CM~∞	<+0.25%	9*9*7	503776-2420 24pin	503772-2420	IR 850
		SF-XNXS9282V10V1 940nm	MIPI	FF	1/4"	TBD	2.0	150	10CM~∞	<27%	9*9*7	503776-2420 24pin	503772-2420	IR 940
	OV10640	SF-COV10640MIPI-HDR-30L	MIPI	FF	1/2.56"	6	2.0	H55	TBD	<9%	22*15*24.7	0.5mm golden finger 30pin	FH12-30S-0.5SH	
	BF314ACS	SF3F314ACBOC	MIPI	FF	1/4"	5.54	2.4	D44.6	40CM~1M	<1.5%	9*9*6.15	golden finger 24pin	TBD	
IMX678	SF-CTSE830	MIPI	AF	1/1.8"	5.8	2.2	76	1M~∞	<-2.4%	50*22*33.41	golden finger 26pin	TBD	650nm IR Cut	
IMX678	SF3X678BA	MIPI	FF	1/1.8"	4	2	D133	1M~∞	<-35%	20*20*9.42	golden finger 30pin	TBD		
OG01A1B	SF-V01A1B3	MIPI	FF	1/5"	TBD	2.2	D130	30cm~∞	<15%	6.5*6.5*4.5	5052742040_2 20pin	TBD		
OV7675	SF030-OV7675A	DVP	FF	1/9"	1.7	2.8	60	TBD	<1%	6*6*3.8	0.5mm golden finger 24pin	FH12-24S-0.5SH		
OV7740	SF-AOV7740-WL05-F5	DVP	FF	1/5"	2.56	2.8	65/58/38	15CM~∞	<1%	6.5*6.5*3.9	0.5mm golden finger 24pin	FH12-24S-0.5SH	YUV	
OV7740	SF-V77401	DVP	FF	1/5"	TBD	2.0	D180; H155	200CM	>53%	13.4*13.4*13.77	golden finger 24pin	TBD		
OV7740	SF-030RSM7740BY	DVP	FF	1/5"	TBD	2.8	D130, H100	TBD	<-5%	10*10*4.1	golden finger 24pin	TBD		
OV7725	SF-C03140V-WB01 V1.1	DVP	FF	1/4"	4.39	2.4	60	60CM~∞	<1%	8*8*5.65	0.5mm golden finger 24pin	FH12-24S-0.5SH	YUV	
	SF3V7725BA	DVP	FF	1/4"	2.6	2.6	112	15CM~∞	<-20%	13*13*8.93	golden finger 24pin	TBD		

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F.NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
0.3MP	OV7670	SF-AOV7670-YE03	DVP	FF	1/9"	1.55	2.8	60	30CM~∞	<1%	6*6*3.7	0.5mm golden finger 20pin	FH12-20S-0.5SH	LED
	OV7670	SF-FV76703	DVP	FF	1/6"	TBD	2.8	28.7	TBD	<1%	10*10*5	golden finger 24pin	TBD	
	OV7251	SF-ASV7251	MIPI	FF	1/7.5"	2.66	2.8	H39	30CM~∞	<-20.77%	6*6*4.3	AXT624124 24pin	AXT524124	
		SF-7251-H106	MIPI	FF	1/7.5"	0.74	2.0	120/106/88.8	5CM~∞	<10%	6*6*5.8	AXT624124 24pin	AXT524124	
		SF-C72510V-H133-BTB-L40	MIPI	FF	1/7.5"	0.83	2.0	166/133/100	5CM~∞	<-20.77%	6.45*6.45*5.5	AXT624124 24pin	AXT524124	
		SF-C03170V-M7-120L	MIPI	FF	1/7.5"	2	2.5	H42	30CM~∞	<3%	8*8*12.35	0.5mm golden finger 24pin	FH12-24S-0.5SH	
		SF-C03170V-H75-8inch	MIPI	FF	1/7.5"	1.27	2.4	H75	60CM~∞	<-15%	6.5*6.5*5	AXT624124	AXT524124	
		SF-V7251	MIPI	FF	1/7.5"	/	2.4	H56.8° V44° D77°	8CM~∞	<1%	5*5*3.25	OK-14GM030-04 30pin	OK-14GF030-04	
		SF-V7252	MIPI	FF	1/7.5"	/	4.5	H37.2° V28.4° D45.8	8CM~∞	<1%	5.5*5.5*3.05	OK-14GM030-04 30pin	OK-14GF030-04	
		GC0382	SF-C0328GC-J5F V1.0	DVP	FF	1/6.5"	1.55	2.8	60	30CM~∞	<1%	6*6*4	0.3mm golden finger 21pin	FH26-21S-0.3SHW
	SF-C0328GC-HT01F V1.0		DVP	FF	1/6.5"	1.55	2.8	60	30CM~∞	<1%	6*6*4	0.3mm golden finger	FH26-21S-0.3SHW	
	GC0310	SF-C0310GC-7298B V1.0	MIPI	FF	1/10"	1.55	2.8	60	30CM~∞	<1%	8.5*8.5*5	0.5mm golden finger	FH12-20S-0.5SH	
		SF-LG5240	MIPI	FF	1/13"	TBD	2.8	D54	1.5CM	<1.5%	5*5*2.9	golden finger 25pin	TBD	
	GC0309	SF-YM0312	DVP	FF	1/9"	1.8	2.8	62°	30CM~∞	<1%	6.5*6.5	5.009A0-024-1R0 24pin	TBD	
	GC0308	SF-C0308GC-M3PRO	DVP	FF	1/6.5"	2.75	2.8	60	30CM~∞	<1%	6*6*3.7	0.5mm golden finger 20pin	FH12-20S-0.5SH	
		SF-C0308GC-ZIF-650&940-64L	DVP	FF	1/6.5"	2.63	2.2	60	30CM~∞	<1%	6*6*3.7	0.5mm golden finger 24pin	FH12-24S-0.5SH	
		SF-C0308GC-JH-C3 V1.0	DVP	FF	1/6.5"	1.85	2.8	60	30CM~∞	<1%	6*6*3.7	0.5mm golden finger	FH12-20S-0.5SH	
	GC6133	SF-SPI6133	MIPI	FF	1/13"	TBD	2.8	60	20CM-80CM	<0.7%	5*5*3	OK-06M010-04 10pin	OK-06F010-04	
		SF-GC6133-Q1-6611	MIPI	FF	1/13"	1.4	3	60	TBD	<1%	5.5*5.5*3	golden finger 18pin	TBD	LED
	HM0360	SF3M036A08	MIPI	FF	1/6"	2.85	2.8	52	20CM~∞	<-3%	6.5*6.5*3.97	AXE626124 26pin	TBD	
SC031GC	SF-C505H-V1	MIPI	FF	1/6"	TBD	2.4	D88.8	15-30mm	<1.5%	23.1*6.5*3.85	golden finger 25pin	TBD	LED	

SINCEREFIRST FPC Camera Module List

像素 Pixel	感光芯片 Sensor	型号 Module	接口 Interface	对焦 Focusing	芯片尺寸 Size	镜头焦距 EFL	光圈 F. NO	视场角 ViewAngle	景深 FocusRange	畸变 Distortion	模组尺寸 Module Size	模组连接器型号 Connector	匹配连接器号 Match Connector	备注 Notes
	BF20A1	SF-S020A1-S6-B2-F V1.1	MIPI	FF	1/10"	1.8	3	64	20CM~0.6M	<1.5%	6.5*6.5*5.5mm	OK-F302-25115 25pin	TBD	
	GC032A	SF-S032A-T6150-B SUB V1.1	MIPI	/	1/10"	/	/	/	/	/	5.0*5.0*3.0mm	CFPC0310-21RL-TAG 21pin	TBD	
	BF20A6	SF-PCOWN0001B	MIPI	AF	1/10"	1	3	D75	40MM~∞	<1.5%	6.5*6.5*4.25	golden finger 25pin	TBD	
0.8MP	BF30A2	SF-S030A2-W31	DVP	FF	1/15"	1.44	3	70	20CM~0.6M	<1.5%	5.0*5.0*3.0mm	golden finger 24pin	TBD	
0.1MP	GC6153	SF6153	DVP	FF	1/13"	TBD	2.8	62	30CM~40CM	<0.7%	5*5*3.35	0.5mm golden finger 24pin	0.5S-AL-24PWB	

New products are being updated continuously.

GUANGZHOU SINCERE INFORMATION TECHNOLOGY LTD. All Right Reserved
 sales@sincerefirst.com
 SincereFirst.com / CameraModule.cn

***The lens angle of all products is not fixed and it can be matched with different lenses according to customer requirements.

This Camera Module list is for reference only. For more products updates (like USB cmos camera module, Endoscope Camera Module, IP Camera Module), please contact our company or your direct sales manager. Thank you for your support of our company and products. We will always take the customer first, quality first, and sincere first as the foundation of our company. Welcome your cooperation. SincereFirst, Sincere is Frst!