

産業用&民生用のBOE製LCDモジュール 2026Q1

▶赤色：主力商品

Serial	SIZE	FG-Code	Resolution	Interface	Brightness	Contrast ratio	Color depth	Color Gamut	Viewing Angle	LED Life-Time	Operating Temp	Active area	Outline	7×24時間 点灯対応	備考
1	10.1	EV101WXM-N10	WXGA(1280*800)	LVDS	400nit	900:1	6bit+FRC	50%	85/85/85/85	30Kh	-20~70℃	216.96*135.6	228.6*149.2*3.0		
2	10.1	EV101WXM-N80	WXGA(1280*800)	LVDS	400nit	900:1	6bit+FRC	48%	85/85/85/85	30Kh	-20~70℃	216.96*135.6	232.2*152.9*10.4		
3	10.1	GV101WXM-N80	WXGA(1280*800)	LVDS	500nit	1300:1	8bit	45%	85/85/85/85	30Kh	-20~70℃	216.96*135.6	228.2*148.85*4.9		
4	10.1	GV101WXM-N40	WXGA(1280*800)	EDP	1000nit	1000:1	6bit+FRC	50%	80/80/80/80	30Kh	-20~70℃	216.576*135.36	228.2*149.5*1.1		
5	10.4	ET104S0M-N15	SVGA(800*600)	LVDS	350nit	800:1	6bit+FRC	55%	65/75/80/80	30Kh	-20~70℃	211.2*158.4	236*176.9*5.6		
6	10.4	ET104S0M-N16	SVGA(800*600)	LVDS	350nit	800:1	6bit+FRC	55%	65/75/80/80	30Kh	-20~70℃	211.2*158.4	236*176.9*5.6		
7	10.4	GV104X0M-N10	XGA(1024*768)	LVDS	450nit	1100:1	8bit	70%	85/85/85/85	50Kh	-30~85℃	210.432*157.824	230*180.2*10.5		
8	12.1	ET121S0M-N14	SVGA(800*600)	LVDS	400nit	800:1	6/8bit	55%	65/75/80/80	30Kh	-20~70℃	246*184.5	279*209*9		
9	12.1	EV121WXM-N12	WXGA(1280*800)	LVDS	500nit	1200:1	6/8bit	72%	85/85/85/85	50Kh	-20~72℃	261.12*163.20	277.7*180.6*9.2		
10	12.1	EV121WXM-N16	WXGA(1280*800)	LVDS	400nit	1200:1	6/8bit	72%	85/85/85/85	50Kh	-20~70℃	261.12*163.20	278*184*6.7		
11	12.1	GV121WXM-N80	WXGA(1280*800)	LVDS	450nit	1000:1	6/8bit	50%	85/85/85/85	50Kh	-20~70℃	262.656*164.16	278*184*9.91		
12	12.1	PV121X0M-N10	XGA(1024*768)	LVDS	500nit	1200:1	8bit	72%	85/85/85/85	50Kh	-20~70℃	245.76*184.32	260.5*204*8.7		
13	15.0	DV150X0M-N10	XGA(1024*768)	LVDS	350nit	1000:1	8bit	72%	89/89/89/89	50Kh	-20~70℃	304.128*228.096	326.5*253.5*9.7	対応	
14	15.0	DV150X0M-N11	XGA(1024*768)	LVDS	350nit	1000:1	6bit	72%	89/89/89/89	50Kh	-20~70℃	304.128*228.096	326.5*253.5*9.7	対応	
15	15.0	DV150X0M-N12	XGA(1024*768)	EDP	350nit	1000:1	6bit+FRC	72%	89/89/89/89	50Kh	-20~70℃	304.128*228.096	326.5*253.5*9.7	対応	
16	15.0	DV150X0M-N16	XGA(1024*768)	LVDS	600nit	1000:1	8bit	72%	89/89/89/89	50Kh	-20~70℃	304.128*228.096	326.5*253.5*10.4	対応	
17	15.0	DV150X0M-N17	XGA(1024*768)	LVDS	1500nit	1000:1	8bit	72%	89/89/89/89	50Kh	-30~80℃	304.13*228.1	326.5*253.5*7.85/12.4	対応	
18	15.0	DV150X0M-N18	XGA(1024*768)	EDP	350nit	1000:1	6bit+FRC	72%	89/89/89/89	50Kh	-20~70℃	304.13*228.1	314.13*245.3*4.85	対応	
19	15.6	EV156FHM-N10	FHD(1920*1080)	EDP	500nit	1200:1	6bit+FRC	79%	89/89/89/89	50Kh	0~70℃	344.16*193.59	363.8*215.9*9.6		
20	15.6	EV156FHM-N12	FHD(1920*1080)	LVDS	500nit	1200:1	8bit	72%	85/85/85/85	30Kh	-20~70℃	345.6*194.4	363.8*215.9*9.6		
21	15.6	PT156WHM-N10	WXGA(1366*768)	EDP	400nit	500:1	6bit	45%	45/45/20/40	30Kh	0~50℃	344.23*193.54	359.5*206.5*3.2		
22	15.6	NT156WHM-N42	WXGA(1366*768)	EDP	220nit	500:1	6bit+FRC	45%	45/45/20/40	15Kh	0~50℃	344.23*193.54	359.5*223.8*3.2		
23	15.6	NV156FHM-N48	FHD(1920*1080)	EDP	250nit	800:1	6bit+FRC	45%	85/85/85/85	15Kh	0~50℃	344.16*193.59	350.66*216.245*3.2		
24	17.0	DV170E0M-N10	SXGA(1280*1024)	LVDS	250nit	1000:1	6bit+FRC	72%	89/89/89/89	30Kh	0~50℃	337.92*270.336	358.5*296.5*10.3		
25	17.0	DV170E0M-N30	SXGA(1280*1024)	LVDS	500nit	1000:1	6bit+FRC	72%	89/89/89/89	30Kh	-20~70℃	337.92*270.336	358.5*296.5*8.7		
26	17.0	DV170VGM-N10	QVGA(1280*960)	LVDS	250nit	1000:1	8bit	72%	89/89/89/89	30Kh	0~50℃	345.408*259.056	359*284.8*13.3		
27	18.4	EV184QUM-N80	4K(3840*2160)	EDP	1000nit	1000:1	8bit+FRC	80%	85/85/85/85	30Kh	0~50℃	408.96*230.04	431*255.9*10		
28	18.5	DV185WHM-NM1	WXGA(1366*768)	LVDS	250nit	1000:1	8bit	75%	89/89/89/89	30Kh	0~50℃	409.8*230.4	430.4*254.6*10.9		
29	18.5	DV185WHM-NM2	WXGA(1366*768)	LVDS	500nit	1000:1	8bit	75%	89/89/89/89	50Kh	0~50℃	409.8*230.4	430.4*254.6*10.9		
30	18.5	GV185FHM-N10	FHD(1920*1080)	LVDS	350nit	1000:1	8bit	70%	85/85/85/85	50Kh	-30~80℃	408.96*230.04	430.4*254.6*12		
31	19.0	DV190E0M-N11	SXGA(1280*1024)	LVDS	250nit	1000:1	8bit	72%	89/89/89/89	30Kh	0~50℃	374.784*299.827	396*324*10.4		
32	19.0	ZV190E0M-N10	SXGA(1280*1024)	LVDS	450nit	1000:1	8bit	90%	89/89/89/89	50Kh	-20~70℃	374.784*299.827	396*324*12.55		
33	19.0	GV190FHM-N10	FHD(1920*960)	LVDS	300nit	1200:1	6bit+FRC	72%	89/89/89/89	30Kh	0~50℃	476.64*89.37	491.5*109.4*8.4	ハーフ	
34	21.5	GV215FHM-N10	FHD(1920*1080)	LVDS	350nit	1000:1	6bit+FRC	72%	85/85/85/85	30Kh	-20~70℃	476.64*268.11	495.6*292.2*10.7		
35	21.5	HR215WU1-120	FHD(1920*1080)	LVDS	250nit	1000:1	8bit	72%	89/89/89/89	30Kh	0~50℃	476.064*267.786	495.6*292.2*10.7		
36	21.5	DV215FHM-N40	FHD(1920*1080)	LVDS	500nit	1000:1	8bit	73%	89/89/89/89	30Kh	0~50℃	476.064*267.786	495.6*292.2*10.7		
37	21.5	DV215FHM-R10	FHD(1920*1080)	LVDS	1500nit	1000:1	6bit+FRC	72%	89/89/89/89	50Kh	-20~60℃	478.66*260.28	499*286.2*10.7		
38	23.6	DV236FHM-N00	丸型：1280*1280	LVDS	1500nit	1000:1	8bit	72%	89/89/89/89	50Kh	-20~70℃	599.424*599.424	657*657*28.65	対応	
39	23.8	DV238FHM-P20	FHD(1920*1080)	LVDS	300nit	1000:1	6bit+FRC	72%	89/89/89/89	30Kh	-5~60℃	527.04*296.46	543*316*11.7		
40	24.0	EV240WUM-N10	WXGA(1920*1200)	LVDS	600nit	1000:1	8bit	72%	89/89/89/89	50Kh	0~50℃	518.4*324	546.4*352.0*12.7		
41	24.0	GV240FHM-N10	FHD(1920*960)	LVDS	300nit	1200:1	6bit+FRC	72%	89/89/89/89	30Kh	0~50℃	597.888*112.104	612.7*132.1*12.8	ハーフ	
42	27.0	DV270FHM-R01	FHD(1920*1080)	LVDS	1500nit	1000:1	8bit	72%	89/89/89/89	50Kh	-20~80℃	597.888*336.312	626*363.8*9.3		
43	27.0	DV270FHM-P20	FHD(1920*1080)	LVDS	300nit	1000:1	8bit	72%	89/89/89/89	30Kh	0~50℃	597.888*336.312	630*368*9.5	対応	
44	27.0	DV270QUM-R10	UHD(3840*2160)	EDP	1000nit	1200:1	10bit	72%	89/89/89/89	50Kh	-20~60℃	596.736*335.664	623.3*362.3*9.5	対応	
45	28.0	DV280FHM-NB1	FHD(1920*960)	LVDS	700nit	1200:1	8bit	72%	89/89/89/89	30Kh	0~60℃	699.84*131.22	732*165*16.8		
46	29.0	DV290FHM-N10	FHD(1920*540)	LVDS	700nit	1200:1	8bit	72%	89/89/89/89	50Kh	-5~60℃	705.6*198.45	720.8*226.25*8.4		
47	32.0	DV320FHM-N40	FHD(1920*1080)	LVDS	400nit	1200:1	8bit	72%	89/89/89/89	30Kh	0~50℃	696.4*392.85	716.2*415.05*7.1		
48	35.0	DV350FHM-N10	UHD(3840*×200)	VbyOne	500nit	1000:1	8bit+FRC	72%	89/89/89/89	50Kh	0~50℃	877.824*45.72	891.6*60.4*10		
49	37.0	DV370FHM-N10	FHD(1920*540)	LVDS	700nit	1000:1	8bit	72%	89/89/89/89	50Kh	0~50℃	899.712*253.044	914.9*280.9*22.7		
50	43.0	DV430FHM-NN1	FHD(1920*1080)	LVDS	400nit	1200:1	8bit	72%	89/89/89/89	30Kh	0~50℃	940.896*529.254	962.1*550.5*12.9		
51	43.0	DV430QUM-N10	UHD(3840*2160)	VbyOne	500nit	1200:1	8bit+FRC	72%	89/89/89/89	30Kh	0~50℃	941.194*529.416	962.1*550.5*12.9	対応	
52	43.1	PV431DBM-N10	UHD(3840*720)	VbyOne	1000nit	1000:1	8bit	60%	85/85/85/85	50Kh	-20~70℃	1073.664*201.312	1112.3*228.5*19.3	ハーフ	
53	49.0	DV490FHM-NN3	FHD(1920*1080)	LVDS	400nit	1200:1	8bit	68%	89/89/89/89	30Kh	0~50℃	1073.8*604	1090.4*621.3*27.355		
54	55.0	DV550QUM-N10	UHD(3840*2160)	VbyOne	800nit	1200:1	8bit+FRC	74%	89/89/89/89	50Kh	0~50℃	1209.6*680.4	1232.4*703.2*17		
55	65.0	DV650QUM-N00	UHD(3840*2160)	VbyOne	500nit	1200:1	8bit+FRC	72%	89/89/89/89	50Kh	0~50℃	1428.48*803.52	1450.38*825.47*50.9		
56	75.0	DV750QUM-R11	UHD(3840*2160)	VbyOne	3500nit	1200:1	8bit+FRC	72%	89/89/89/89	50Kh	-20~60℃	1649.664*927.936	1675.7*956.1*66.8		